

AQUAPRO OUTDOORS PLUS DECKING

Polycure - A division of Era Polymers Pty Ltd

Version No: 2.2

Safety Data Sheet according to Work Health and Safety Regulations (Hazardous Chemicals) 2023 and ADG requirements

Initial Date: 29/08/2025 Revision Date: 18/09/2025 Print Date: 18/09/2025 S.GHS.AUS.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Prodi	104	Idan	4ifiar

Product name	AQUAPRO OUTDOORS PLUS DECKING	
Synonyms	Not Available	
Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains 2-octyl-4-isothiazolin-3-one)		

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	A premium oil-based coating for exterior	decking and walkways
--------------------------	--	----------------------

Details of the manufacturer or importer of the safety data sheet

Registered company name	Polycure - A division of Era Polymers Pty Ltd	
Address	2-4 Green Street, Banksmeadow, 2019, NSW, Australia	
Telephone	+612 9666 3888	
Fax	+612 9666 4805	
Website	www.polycure.com.au	
Email	erapol@erapol.com.au	

Emergency telephone number

Association / Organisation	CHEMWATCH EMERGENCY RESPONSE (24/7)	
Emergency telephone number(s)	+61 1800 951 288 (ID#: 9-c60868)	
Other emergency telephone number(s)	+61 3 9573 3188	

SECTION 2 Hazards identification

Classification of the substance or mixture

HAZARDOUS CHEMICAL. DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

Poisons Schedule	Not Applicable
Classification [1] Sensitisation (Skin) Category 1A, Hazardous to the Aquatic Environment Acute Hazard Category 2, Hazardous to the Aquatic Environment Acute Hazard Category 2, Hazardous to the Aquatic Environment Acute Hazard Category 2, Hazardous to the Aquatic Environment Acute Hazard Category 2, Hazardous to the Aquatic Environment Acute Hazard Category 2, Hazardous to the Aquatic Environment Acute Hazard Category 2, Hazardous to the Aquatic Environment Acute Hazard Category 2, Hazardous to the Aquatic Environment Acute Hazard Category 2, Hazardous to the Aquatic Environment Acute Hazard Category 2, Hazardous to the Aquatic Environment Acute Hazard Category 2, Hazardous to the Aquatic Environment Acute Hazard Category 2, Hazardous to the Aquatic Environment Acute Hazard Category 2, Hazardous to the Aquatic Environment Acute Hazard Category 2, Hazardous to the Aquatic Environment Acute Hazard Category 2, Hazardous to the Aquatic Environment Acute Hazard Category 2, Hazardous to the Aquatic Environment Acute Hazard Category 2, Hazardous to the Aquatic Environment Acute Hazard Category 2, Hazardous to the Aquatic Environment Acute Hazard Category 2, Hazardous to the Aquatic Environment Acute Hazardous to the	
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

Label elements

Hazard pictogram(s)





Signal word

Warning

Hazard statement(s)

H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statement(s) General

P101	P101 If medical advice is needed, have product container or label at hand.	
P102	Keep out of reach of children.	

Version No: 2.2 Page 2 of 10

AQUAPRO OUTDOORS PLUS DECKING

Initial Date: 29/08/2025 Revision Date: 18/09/2025 Print Date: 18/09/2025

P103	Read carefully and follow all instructions.	
Precautionary statement(s) Prevention		
P280	Wear protective gloves and protective clothing.	
P261	Avoid breathing mist/vapours/spray.	
P273 Avoid release to the environment.		
P272	Contaminated work clothing should not be allowed out of the workplace.	

Precautionary statement(s) Response

P302+P352	IF ON SKIN: Wash with plenty of water.	
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.	
P362+P364	Take off contaminated clothing and wash it before reuse.	
P391	Collect spillage.	

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
------	--

No further product hazard information.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
26530-20-1	<0.1	2-octyl-4-isothiazolin-3-one
Not Available	to 100	All other substances - non-hazardous
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available	

SECTION 4 First aid measures

Description of first aid measures

Eye Contact	If this product comes in contact with eyes: Wash out immediately with water. If irritation continues, seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

Extinguishing media

- ▶ Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.
- Water spray or fog Large fires only.

Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.	
Advice for firefighters		
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water courses. Use fire fighting procedures suitable for surrounding area. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use. 	
Fire/Explosion Hazard	▶ Non combustible.	

Version No: 2.2 Page 3 of 10

AQUAPRO OUTDOORS PLUS DECKING

Initial Date: 29/08/2025 Revision Date: 18/09/2025 Print Date: 18/09/2025

▶ Not considered a significant fire risk, however containers may burn. HAZCHEM

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	Environmental hazard - contain spillage. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite. Wipe up. Place in a suitable, labelled container for waste disposal.
Major Spills	Environmental hazard - contain spillage. Minor hazard. Clear area of personnel. Alert Fire Brigade and tell them location and nature of hazard. Control personal contact with the substance, by using protective equipment as required. Prevent spillage from entering drains or water ways. Contain spill with sand, earth or vermiculite. Collect recoverable product into labelled containers for recycling. Absorb remaining product with sand, earth or vermiculite and place in appropriate containers for disposal. Wash area and prevent runoff into drains or waterways. If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling	
Safe handling	 Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Avoid contact with moisture. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Launder contaminated clothing before re-use. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained. DO NOT allow clothing wet with material to stay in contact with skin
Other information	 Store in original containers. Keep containers securely sealed. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS.

Conditions for safe storage, including any incompatibilities

Suitable container	 Polyethylene or polypropylene container. Packing as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.
Storage incompatibility	None known

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Not Available

Ingredient	Original IDLH	Revised IDLH
2-octyl-4-isothiazolin-3-one	Not Available	Not Available

Exposure controls

Appropriate engineering

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard 'physically' away from the worker and ventilation that strategically 'adds' and 'removes' air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The

Version No: 2.2 Page 4 of 10 Initial Date: 29/08/2025

AQUAPRO OUTDOORS PLUS DECKING

Revision Date: 18/09/2025 Print Date: 18/09/2025

design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure.

General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying 'escape' velocities which, in turn, determine the 'capture velocities' of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air)	0.25-0.5 m/s (50- 100 f/min)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100- 200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200- 500 f/min)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5-10 m/s (500- 2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood - local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Individual protection measures, such as personal protective equipment











Eye and face protection

- Safety glasses with side shields
- Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 591.

Skin protection

See Hand protection below

Hands/feet protection

- Wear chemical protective gloves, e.g. PVC.
- Wear safety footwear or safety gumboots, e.g. Rubber

NOTE:

- ▶ The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
- ▶ Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:

- frequency and duration of contact, chemical resistance of glove material,
- glove thickness and
- dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).

· When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than

- 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
- When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
- Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.
- Contaminated gloves should be replaced.

As defined in ASTM F-739-96 in any application, gloves are rated as:

- · Excellent when breakthrough time > 480 min
- Good when breakthrough time > 20 min
- Fair when breakthrough time < 20 min
- Poor when glove material degrades

For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.

Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

Version No: 2.2 Page 5 of 10 Initial Date: 29/08/2025

AQUAPRO OUTDOORS PLUS DECKING

Revision Date: 18/09/2025 Print Date: 18/09/2025

	Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of. Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.
Body protection	See Other protection below
Other protection	 Overalls. P.V.C apron. Barrier cream. Skin cleansing cream. Eye wash unit.

Respiratory protection

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Required minimum protection factor	Maximum gas/vapour concentration present in air p.p.m. (by volume)	Half-face Respirator	Full-Face Respirator
up to 10	1000	A-AUS / Class1 P2	-
up to 50	1000	-	A-AUS / Class 1 P2
up to 50	5000	Airline *	-
up to 100	5000	-	A-2 P2
up to 100	10000	-	A-3 P2
100+			Airline**

* - Continuous Flow ** - Continuous-flow or positive pressure demand A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Liquid		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available
Heat of Combustion (kJ/g)	Not Available	Ignition Distance (cm)	Not Available
Flame Height (cm)	Not Available	Flame Duration (s)	Not Available
Enclosed Space Ignition Time Equivalent (s/m3)	Not Available	Enclosed Space Ignition Deflagration Density (g/m3)	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Version No: 2.2 Page 6 of 10 Initial Date: 29/08/2025

AQUAPRO OUTDOORS PLUS DECKING

Revision Date: 18/09/2025 Print Date: 18/09/2025

Information on toxicological effects

a) Acute Toxicity	Based on available data, the classification criteria are not met.				
b) Skin Irritation/Corrosion	Based on available data, the classification criteria are not met.				
c) Serious Eye Damage/Irritation	Based on available data, the classification criteria are not met.				
d) Respiratory or Skin sensitisation	There is sufficient evidence to classify this material as sensitising to skin or the respiratory system				
e) Mutagenicity	Based on available data, the classification criteria are n	ot met.			
f) Carcinogenicity	Based on available data, the classification criteria are n	ot met.			
g) Reproductivity	Based on available data, the classification criteria are n	ot met.			
h) STOT - Single Exposure	Based on available data, the classification criteria are n	ot met.			
i) STOT - Repeated Exposure	Based on available data, the classification criteria are n	ot met.			
j) Aspiration Hazard	Based on available data, the classification criteria are n	ot met.			
Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.				
Ingestion	The material has NOT been classified by EC Directives of corroborating animal or human evidence.	or other classific	cation systems as 'harmful by ingestion'. This is because of the lack		
Skin Contact			tation following contact (as classified by EC Directives using animal e kept to a minimum and that suitable gloves be used in an		
Eye	Although the liquid is not thought to be an irritant (as cladiscomfort characterised by tearing or conjunctival redn		irectives), direct contact with the eye may produce transient dburn).		
Chronic	Skin contact with the material is more likely to cause a	sensitisation read	ction in some persons compared to the general population.		
AQUAPRO OUTDOORS PLUS	TOXICITY		IRRITATION		
DECKING	Not Available		Not Available		
	TOVIOLEY	IDDITATION			
	TOXICITY IRRITATION				
	roi				
	Dermal (rabbit) LD50: 311 mg/kg ^[2]	Eye (Rodent -	rabbit): 100mg - Severe		
	Dermal (rabbit) LD50: 311 mg/kg ^[2] Oral (Rat) LD50: 248 mg/kg ^[2]	,	effect observed (irreversible damage) ^[1]		
2-octyl-4-isothiazolin-3-one	, , , , , , , , , , , , , , , , , , , ,	,	effect observed (irreversible damage) ^[1]		
2-octyl-4-isothiazolin-3-one	, , , , , , , , , , , , , , , , , , , ,	Eye: adverse Skin (Human)	effect observed (irreversible damage) ^[1]		
2-octyl-4-isothiazolin-3-one	, , , , , , , , , , , , , , , , , , , ,	Eye: adverse Skin (Human) Skin (Rodent	effect observed (irreversible damage) ^[1] : 0.1%		
2-octyl-4-isothiazolin-3-one	, , , , , , , , , , , , , , , , , , , ,	Eye: adverse Skin (Human) Skin (Rodent Skin: adverse	effect observed (irreversible damage) ^[1] : 0.1% - rabbit): 500mg/24H effect observed (corrosive) ^[1]		
2-octyl-4-isothiazolin-3-one	, , , , , , , , , , , , , , , , , , , ,	Eye: adverse Skin (Human) Skin (Rodent Skin: adverse	effect observed (irreversible damage) ^[1] : 0.1% - rabbit): 500mg/24H		
2-octyl-4-isothiazolin-3-one Legend:	Oral (Rat) LD50: 248 mg/kg ^[2]	Eye: adverse Skin (Human) Skin (Rodent Skin: adverse Skin: adverse	effect observed (irreversible damage) ^[1] : 0.1% - rabbit): 500mg/24H effect observed (corrosive) ^[1] effect observed (irritating) ^[1] exicity 2. Value obtained from manufacturer's SDS. Unless otherwise		
	Oral (Rat) LD50: 248 mg/kg ^[2] 1. Value obtained from Europe ECHA Registered Subst	Eye: adverse Skin (Human) Skin (Rodent Skin: adverse Skin: adverse	effect observed (irreversible damage) ^[1] : 0.1% - rabbit): 500mg/24H effect observed (corrosive) ^[1] effect observed (irritating) ^[1] exicity 2. Value obtained from manufacturer's SDS. Unless otherwise		
	Oral (Rat) LD50: 248 mg/kg ^[2] 1. Value obtained from Europe ECHA Registered Subsispecified data extracted from RTECS - Register of Toxion ROHM & HAAS Data ADI: 0.03 mg/kg/day NOEL: 60 m Asthma-like symptoms may continue for months or ever condition known as reactive airways dysfunction syndro compound. Main criteria for diagnosing RADS include to for persistent asthma-like symptoms within minutes to hinclude a reversible airflow pattern on lung function test and the lack of minimal lymphocytic inflammation, without disorder with rates related to the concentration of and disorder w	Eye: adverse Skin (Human) Skin (Rodent Skin: adverse Skin: adverse Skin: adverse Skin: adverse Skin: adverse Skin: adverse stances - Acute to to Effect of chemic g/kg/day nne (RADS) which he absence of prours of a docume s, moderate to s to suit eosinophilia. Jurration of expos high concentration	effect observed (irreversible damage) ^[1] : 0.1% - rabbit): 500mg/24H effect observed (corrosive) ^[1] effect observed (irritating) ^[1] exicity 2. Value obtained from manufacturer's SDS. Unless otherwise ical Substances cosure to the material ends. This may be due to a non-allergic ch can occur after exposure to high levels of highly irritating revious airways disease in a non-atopic individual, with sudden onset ented exposure to the irritant. Other criteria for diagnosis of RADS evere bronchial hyperreactivity on methacholine challenge testing, RADS (or asthma) following an irritating inhalation is an infrequent ure to the irritating substance. On the other hand, industrial bronchitis ons of irritating substance (often particles) and is completely		
Legend: 2-OCTYL-4-ISOTHIAZOLIN-3-	Oral (Rat) LD50: 248 mg/kg ^[2] 1. Value obtained from Europe ECHA Registered Subst specified data extracted from RTECS - Register of Toxion ROHM & HAAS Data ADI: 0.03 mg/kg/day NOEL: 60 m Asthma-like symptoms may continue for months or everondition known as reactive airways dysfunction syndro compound. Main criteria for diagnosing RADS include to finclude a reversible airflow pattern on lung function test and the lack of minimal lymphocytic inflammation, with disorder with rates related to the concentration of and dis a disorder that occurs as a result of exposure due to I reversible after exposure ceases. The disorder is charated the following information refers to contact allergens as Contact allergies quickly manifest themselves as contact contact eczema involves a cell-mediated (T lymphocyte urticaria, involve antibody-mediated immune reactions. potential: the distribution of the substance and the oppowhich is widely distributed can be a more important alle	Eye: adverse Skin (Human) Skin (Rodent Skin: adverse stances - Acute to to Effect of chem. g/kg/day n years after exp me (RADS) white pours of a docume s, moderate to s out eosinophilia. I uration of expos high concentratio cterized by diffic a group and may ct eczema, more s) immune react The significance ortunities for cont rgen than one w	effect observed (irreversible damage) ^[1] : 0.1% - rabbit): 500mg/24H effect observed (corrosive) ^[1] effect observed (irritating) ^[1] exicity 2. Value obtained from manufacturer's SDS. Unless otherwise ical Substances cosure to the material ends. This may be due to a non-allergic ch can occur after exposure to high levels of highly irritating revious airways disease in a non-atopic individual, with sudden onset ented exposure to the irritant. Other criteria for diagnosis of RADS revere bronchial hyperreactivity on methacholine challenge testing, RADS (or asthma) following an irritating inhalation is an infrequent ure to the irritating substance. On the other hand, industrial bronchitis ons of irritating substance (often particles) and is completely unty breathing, cough and mucus production.		

Legend:

X − Data either not available or does not fill the criteria for classification
 y − Data available to make classification

×

Carcinogenicity

Reproductivity

Aspiration Hazard

STOT - Single Exposure

STOT - Repeated Exposure

Acute Toxicity

Serious Eye

sensitisation

Mutagenicity

Damage/Irritation Respiratory or Skin

Skin Irritation/Corrosion

Version No: 2.2 Page 7 of 10

AQUAPRO OUTDOORS PLUS DECKING

Initial Date: 29/08/2025 Revision Date: 18/09/2025

Print Date: 18/09/2025

Toxicity

AQUAPRO OUTDOORS PLUS	Endpoint	Test Duration (hr)		Species	Value		Source	
DECKING	Not Available	Not Available	Not Available		Not Ava	ilable	Not Availa	ble
2-octyl-4-isothiazolin-3-one	Endpoint	Test Duration (hr)	Species		Value		Source	
	NOEC(ECx)	840h	Fish			0.009mg/L		4
	EC50	48h	Crustac	Crustacea		0.057-0.178mg	/L	4
	EC50	96h	Algae o	Algae or other aquatic plants		0.15mg/l		2
	LC50	96h	Fish			0.041-0.104mg	/I	4

Leaend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
2-octyl-4-isothiazolin-3-one	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
2-octyl-4-isothiazolin-3-one	LOW (LogKOW = 2.561)

Mobility in soil

Ingredient	Mobility
2-octyl-4-isothiazolin-3-one	LOW (Log KOC = 2120)

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal

- Containers may still present a chemical hazard/ danger when empty.
- ▶ Return to supplier for reuse/ recycling if possible.

Otherwise:

- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
- ▶ Where possible retain label warnings and SDS and observe all notices pertaining to the product.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- ▶ Reuse
- Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

- appropriate.

 DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- Recycle wherever possible or consult manufacturer for recycling options.
- ► Consult State Land Waste Management Authority for disposal
- Bury residue in an authorised landfill.
- ▶ Recycle containers if possible, or dispose of in an authorised landfill.

SECTION 14 Transport information

Labels Required



Marine Pollutant



HAZCHEM

•3Z

Version No: 2.2 Initial Date: 29/08/2025 Page 8 of 10

AQUAPRO OUTDOORS PLUS DECKING

Revision Date: 18/09/2025 Print Date: 18/09/2025

Land transport (ADG)

14.1. UN number or ID number	3082	
14.2. UN proper shipping name	ENVIRONMENTALLY	HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains 2-octyl-4-isothiazolin-3-one)
14.3. Transport hazard class(es)	Class Subsidiary Hazard	9 Not Applicable
14.4. Packing group	Ш	
14.5. Environmental hazard	Environmentally hazar	dous
14.6. Special precautions for user	Special provisions Limited quantity	274 331 335 375 AU01 5 L

Environmentally Hazardous Substances meeting the descriptions of UN 3077 or UN 3082

are not subject to this Code when transported by road or rail in;
(a) packagings;
(b) IBCs; or

- (c) any other receptacle not exceeding 500 kg(L).
- Australian Special Provisions (SP AU01) ADG Code 7th Ed.

Air transport (ICAO-IATA / DGR)

14.1. UN number	3082		
14.2. UN proper shipping name	Environmentally hazardous substance, liquid, n.o.s. (contains 2-octyl-4-isothiazolin-3-one)		
	ICAO/IATA Class	9	
14.3. Transport hazard class(es)	ICAO / IATA Subsidiary Hazard	Not Applicable	
01400(00)	ERG Code	9L	
14.4. Packing group	Ш		
14.5. Environmental hazard	Environmentally hazardous		
	Special provisions		A97 A158 A197 A215
	Cargo Only Packing Instructions		964
	Cargo Only Maximum Qty / Pack		450 L
14.6. Special precautions for user	Passenger and Cargo Packing Instructions		964
	Passenger and Cargo Maximum Qty / Pack		450 L
	Passenger and Cargo Limited Quantity Packing Instructions		Y964
	Passenger and Cargo Limited Ma	aximum Qty / Pack	30 kg G

Sea transport (IMDG-Code / GGVSee)

IRONMENTALLY HA	AZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains 2-octyl-4-isothiazolin-3-one)
IDG Class	9
IDG Subsidiary Haza	ard Not Applicable
ne Pollutant	
MS Number	F-A, S-F
pecial provisions	274 335 969
mited Quantities	5 L
i	ne Pollutant MS Number pecial provisions

14.7. Maritime transport in bulk according to IMO instruments

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
2-octyl-4-isothiazolin-3-one	Not Available
All other substances - non- hazardous	Not Available

14.7.3. Transport in bulk in accordance with the IGC Code

•	
Product name	Ship Type
2-octyl-4-isothiazolin-3-one	Not Available
All other substances - non- hazardous	Not Available

Version No: 2.2 Page 9 of 10

AQUAPRO OUTDOORS PLUS DECKING

Initial Date: 29/08/2025 Revision Date: 18/09/2025 Print Date: 18/09/2025

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

2-octyl-4-isothiazolin-3-one is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6

Australian Inventory of Industrial Chemicals (AIIC)

Additional Regulatory Information

Not Applicable

National Inventory Status

National Inventory Status National Inventory	Status
· · · · · · · · · · · · · · · · · · ·	Jiaus
Australia - AIIC / Australia Non- Industrial Use	Yes
Canada - DSL	Yes
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	All chemical substances in this product have been designated as TSCA Inventory 'Active'
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes
UAE - Control List (Banned/Restricted Substances)	No
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	18/09/2025
Initial Date	29/08/2025

SDS Version Summary

Version	Date of Update	Sections Updated
1.2	18/09/2025	Hazards identification - Classification, Composition / information on ingredients - Ingredients, Name

Other information

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

- ▶ PC TWA: Permissible Concentration-Time Weighted Average
- ▶ PC STEL: Permissible Concentration-Short Term Exposure Limit
- ▶ IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists

- STEL: Short Term Exposure Limit
 TEEL: Temporary Emergency Exposure Limit,
 IDLH: Immediately Dangerous to Life or Health Concentrations
- ES: Exposure Standard
- OSF: Odour Safety Factor
- ▶ NOAEL: No Observed Adverse Effect Level
- LOAEL: Lowest Observed Adverse Effect Level
- TLV: Threshold Limit Value
- LOD: Limit Of Detection
- OTV: Odour Threshold Value
- BCF: BioConcentration Factors
- ▶ BEI: Biological Exposure Index
- DNEL: Derived No-Effect Level
- ▶ PNEC: Predicted no-effect concentration
- MARPOL: International Convention for the Prevention of Pollution from Ships
- ▶ IMSBC: International Maritime Solid Bulk Cargoes Code
- IGC: International Gas Carrier Code
- ▶ IBC: International Bulk Chemical Code
- ▶ AIIC: Australian Inventory of Industrial Chemicals
- ▶ DSL: Domestic Substances List
- ▶ NDSL: Non-Domestic Substances List
- ▶ IECSC: Inventory of Existing Chemical Substance in China

Initial Date: 29/08/2025 Version No: 2.2 Page 10 of 10

AQUAPRO OUTDOORS PLUS DECKING

Revision Date: 18/09/2025 Print Date: 18/09/2025

- EINECS: European INventory of Existing Commercial chemical Substances
 ELINCS: European List of Notified Chemical Substances
- ▶ NLP: No-Longer Polymers
- ▶ ENCS: Existing and New Chemical Substances Inventory

- KECI: Korea Existing Chemicals Inventory
 KZIO: Norea Existing Chemicals Inventory
 NZIoC: New Zealand Inventory of Chemicals
 PICCS: Philippine Inventory of Chemicals and Chemical Substances
 TSCA: Toxic Substances Control Act
- ▶ TCSI: Taiwan Chemical Substance Inventory
- ▶ INSQ: Inventario Nacional de Sustancias Químicas
- NCI: National Chemical Inventory
 FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances