



## FASTASEAL 3030 Clear Sealer

FASTASEAL 3030 is a clear fast drying single pack sealer.

### Product Advantages

- Easy to sand and has excellent adhesion to all timber species
- Efficient isolator to wax extraction problems
- Fast drying product reducing down time between coats
- Excellent flow and levelling results in smooth finish
- Helps keep timber light coloured and closer to its natural appearance

### Typical Applications

Interior use only. Timber, particleboard or cork flooring.

### Product Properties

Build:	Sealer
Sandability:	Excellent
Solvent Resistance:	Sealer
Water Resistance:	Sealer
Levelling & Flow:	Excellent

### Typical Properties

Colour:	Milky
Gloss:	Sealer

### Product Approvals

FASTASEAL 3030 has been evaluated for AS/NZS 4586:2004: Slip resistance classification of new pedestrian surface materials by Advanced Technology Testing & Research (ATTAR). The coating system passed the requirements of the "Dry Slip Resistance" and was classified as Dry = F. Certificates available on request.

### Coverage:

**Base coat:** Timber, Parquetry Floors  
Cork & Particleboard – 12-15 m<sup>2</sup> per litre

### Subsequent coats:

Coverage is dependent upon the porosity of the substrate.

### Thinning:

Not normally required but, if desired, add up to 5% Thinners 3310 or in hot weather add up to 3% Wet Edge Extender 3320.

**Application Methods:**

6mm mohair roller or high quality brush.

**Drying:** Allow 30 minutes to 1 hour to dry before sanding.

*Low temperatures and heavy film thickness will retard drying times. Direct sunlight and draft during drying may affect the final gloss level of the coating.*

**Recommended Sealers:** FASTASEAL 3030 is a sealer

**Application Equipment Clean Up:** Clean all equipment using Super Cleaning Solvent 3300. Ensure all cleaning solvents are removed before placing equipment back in the coating.

**Shelf Life:** 36 months, see label for use by date.

**Packaging:** 20 litres

**Refer to the DURAPOL Product Information Guide for more information.**

**Health & Safety**

Before handling, refer to the Material Safety Data Sheet for health and safety information. Ensure that all personnel using this product have read and understood this data sheet and the associated MSDS and packaging label before using this product.

Note: Coatings give off strong solvents and odours during the drying process. People and pets should be removed from the building during the application and drying of coatings. All food and fabrics should also be removed to reduce the risk of them becoming tainted during the drying process.

---

**Mirotone Pty Ltd Australia (Head Office)**

ABN 40 000 041 136

21 Marigold Street, Revesby NSW 2212, Australia, P +61 2 9795 3700 F +61 2 9771 3601

sales@mirotone.com.au

[www.polycure.com.au](http://www.polycure.com.au)