



## FASTASEAL 3535 Clear Sealer & Recoat Primer

*For use as a clear sealer or for recoating engineered, floating, solid timber or cork floors*

FASTASEAL 3535 Clear Sealer & Recoat Primer, is a versatile clear primer that may be applied in single or two pack form depending upon application requirements.

### Product Advantages

- Low yellowing, reduces initial darkening of timber
- Highly flexible
- Excellent clarity
- No sanding required
- Excellent block to resin exudation and efficient isolator to wax extraction
- Excellent Adhesion, Multiple topcoat options, Barrier Coat

### Typical Applications

Interior use only. Timber, particleboard, engineered flooring or cork flooring.

*Not suitable for exterior or wet area applications e.g. bathrooms or around swimming pools.*

*Caution: floor will be slippery when wet.*

### Product Properties

Build:	Good
Sandability:	Not designed for sanding
Water Resistance:	Excellent especially when mixed with 3535 Part B
Levelling & Flow:	Excellent

### Typical Properties

Colour:	Clear
Gloss:	Sealer/Primer

### Coverage:

Bare Wood:	8-10 m <sup>2</sup> per litre
Recoat:	10-12 m <sup>2</sup> per litre

Coverage is dependent upon the porosity of the substrate.

### Thinning:

Single Pack - not required on bare wood, if desired, add up to 5% Thinners 3310 or in hot weather add up to 3% Wet Edge Extender 3320.

Two Pack recoat – if required add 5-10% Thinners 3310.

DURAPOL 5995 Accelerator may be used to speed up the dry time of FASTASEAL 3535. Add between 2.5 mls of DURAPOL 5995 Accelerator per litre of FASTASEAL 3535. Only mix as much as would be used in one day.

### Mixing Ratio (When used as Two Pack):

Mix FASTASEAL 3535 10A:1B by volume with FASTASEAL 3535 Part B Hardener. Pot life is 4 hours once mixed.



21 Marigold Street, Revesby NSW 2212, Australia, P +61 2 9795 3700 F +61 2 9771 3601  
sales@mirotone.com.au

[www.polycure.com.au](http://www.polycure.com.au)