

FASTASEAL 3030 Clear Sealer

FASTASEAL 3030 is a clear fast drying single pack sealer.

Advantages

- Easy to sand and has excellent adhesion to all timber species
- Efficient isolator to wax extraction problems
- Fast drying product reducing down time between coats
- Excellent flow and levelling results in smooth finish
- Helps keep timber light coloured and closer to its natural appearance

Typical Applications

Interior use only. Timber, particleboard & cork flooring.

Product Approvals

FASTASEAL 3030 has been evaluated for AS/NZS 4586:2004: Slip resistance classification of new pedestrian surface materials by Advanced Technology Testing & Research (ATTAR). The coating system passed the requirements of the "Dry Slip Resistance" and was classified as Dry = F. Certificates available on request.

Coverage

Basecoat :	Timber, Parquetry, Cork & Particleboard	12-15 m ² per litre
Subsequent coats:	Coverage is dependent upon the porosity of the substrate.	

Application Method

By roller or applicator and a high quality brush.

- Roller or Applicator 6mm nap roller.
- Brush

Thinning

Not normally required but, if desired, add up to 5% Thinners 3310 or in hot weather add up to 3% Wet Edge Extender 3320.

Dry Time

Allow 30 minutes to 1 hour to dry before sanding.

Low temperatures and heavy film thickness will retard drying times. Direct sunlight and draft during drying may affect the final gloss level of the coating.

FASTASEAL 3030 Clear Sealer

Fast drying single pack sealer.



Recommended Sealers

FASTASEAL 3030 is a sealer.

Properties	Colour	Milky
	Finish	Sealer
	Build	Sealer
	Sandability	Excellent
	Solvent Resistance	Sealer
	Water Resistance	Sealer
	Levelling & Flow	Excellent
	Pack Sizes	20L
	Product Code	3528-20
	Clean Up	Polycure Super Cleaning Solvent 3300. Ensure all cleaning solvents are removed before placing back in the coating.
	Shelf Life	24 months, see label for use by date. (store in sealed container below 25°C). Do not use product past use by date.

Refer to the FASTASEAL Product Information Guide for more information Health & Safety

Before handling, refer to the Safety Data Sheet for health and safety information. Ensure that all personnel using this product have read and understood this data sheet and the associated SDS and packaging label before using this product.

Note: Coatings give off strong solvents and odours during the drying process. People and pets should be removed from the building during the application and drying of coatings. All food and fabrics should also be removed to reduce the risk of them becoming tainted during the drying process.

POLYCURE a division of Era Polymers Pty Ltd 2-4
Green Street BANKSMEADOW
NSW 2019, Australia P +61 2 96663888 F +61 2 9666 4805

www.polycure.com.au