



# FASTASEAL 3535 Clear Sealer & Recoat Primer

*For use as a clear sealer or for recoating engineered, floating, solid timber or cork floors*

FASTASEAL 3535 Clear Sealer & Recoat Primer, is a versatile clear primer that may be applied in single or two pack from depending upon application requirements.

## Advantages

- Low yellowing, reduces initial darkening of timber
- Highly flexible
- Excellent clarity
- No sanding required
- Excellent block to resin exudation and efficient isolator to wax extraction
- Excellent adhesion, multiple topcoat operations, barrier coat

## Typical Applications

Interior use only. Timber, particleboard, engineered flooring & cork flooring.

*Not suitable for exterior or wet area applications e.g. bathrooms or around swimming pools. Caution: floor will be slippery when wet.*

## Coverage

<b>Basecoat:</b>	Bare Wood	8-10 m <sup>2</sup> per litre
	Recoat	10-12m <sup>2</sup> per litre
<b>Subsequent coats:</b>	Coverage is dependent upon the porosity of the substrate.	

## Application Method

By roller or applicator and a high quality brush.

- Roller or Applicator      6mm mohair roller.
- Brush

## Thinning

<b>Single pack:</b>	Not required on bare wood. If desired, add up to 5% Thinners 3310 or in hot weather add up to 3% Wet Edge Extender 3320.
<b>Two Pack Recoat:</b>	If required add 5-10% Thinners 3310.

DURAPOL 5995 Accelerator may be used to speed up the dry time of FASTASEAL 3535. Add between 2.5mls of DURAPOL 5995 Accelerator per litre of FASTASEAL 3535. Only mix as much as would be used in one day.

## Mixing Ratio (when used as Two Pack):

Mix FASTASEAL 3535 10A:1B by volume with FASTASEAL 3535 Part B Hardener. Pot Life is 4 hours once mixed.

# FASTASEAL 3535

Clear sealer & recoat primer.

---



## Dry Time

**Single Pack:** 1-2 hours

**Two Pack:** Minimum 3 hours

For best results overnight. (Sanding is not required if over coated within 24 hours).

Low temperatures and heavy film thickness will retard drying times. Direct sunlight and draft during drying may affect the final gloss level of the coating.

---

## Application

Preparing the floor to a professional standard is essential to achieve the best results.

### Preparation:

- Fill all nail holes with a water based putty, allow to dry.
- Sand uncoated floor with 120-150 grade sandpaper or screen back on a flexible pad to ensure floor is uniformly dull with no sanding scratches, nibs or fur. Vacuum thoroughly. Take care to avoid scratching the surface.

### Timber, Parquetry, Cork & Particleboard Floor:

- Apply a liberal first coat of FASTASEAL 3535 Sealer (either single pack or two pack) using a 6mm mohair roller and good quality brush to cut in. Allow to dry for 1-2 hours' single pack, 3 hours minimum for two pack.
- Sanding of FASTASEAL 3535 is not recommended. If FASTASEAL 3535 needs to be sanded due to contaminants or defects it could take up to 72 hours to fully dry, particularly in cold temperatures.
- Apply a coat of DURAPOL (gloss only), POLYTHANE (gloss) or AQUAPRO. Allow to dry per instructions on the data sheet.
- If further coats are required, sand floor with 150-180 grade sandpaper or screen back, remove all nibs, fluff and fur. Vacuum all dust.
- Apply the final coat of DURAPOL (gloss or subdued gloss), POLYTHANE (gloss) or AQUAPRO (per datasheet directions).

*Note: Only pour sufficient coating to complete the job, replace the lid immediately as exposure to the environment can cause the product quality and performance to be affected. Ensure all opened cans are used within one week. Do not return unused product to the can as this will cause the remaining material to increase in viscosity.*

---

## Recommended Topcoats

DURAPOL (all gloss levels), POLYTHANE & AQUAPRO.

---

# FASTASEAL 3535

Clear sealer & recoat primer.



## Properties

Colour	Clear	
Finish	Sealer & Primer	
Build	Good	
Sandability	Not designed for sanding	
Water Resistance	Excellent especially when mixed with 3535 Part B	
Levelling & Flow	Excellent	
Pack Sizes	3535 Part A -10L & 20L	3535-B Part B - 1L
Product Code	3535	
Clean Up	Polycure Super Cleaning Solvent 3300. Ensure all cleaning solvents are removed before placing back in the coating.	
Shelf Life	24 months, see label for use by date. (Store in sealed container below 25°C). Do not use product past use by date.	

Refer to the FASTASEAL Product Information Guide for more information.

## Health & Safety

Before handling, refer to the Safety Data Sheet for health and safety information. Ensure that all personnel using this product have read and understood this data sheet and the associated SDS and packaging label before using this product.

Note: Coatings give off strong solvents and odours during the drying process. People and pets should be removed from the building during the application and drying of coatings. All food and fabrics should also be removed to reduce the risk of them becoming tainted during the drying process.

POLYCURE a division of Era Polymers Pty Ltd 2-4  
Green Street BANKSMEADOW  
NSW 2019, Australia P +61 2 96663888 F +61 2 9666 4805

[www.polycure.com.au](http://www.polycure.com.au)