



Need to repair a damaged; conveyor belt, polyurethane or rubber component, waterproofing, mining wear parts such as rotors, impellers or screens?

Think Eratrowel

The **Eratrowel** range is one of **Era Polymers** ancillary products for repairs and is available as a 2 Component MDI or a 3 Component TDI system.

Features of Eratrowel

- Good toughness and abrasion resistance
- Excellent low temperature flexibility
- Good ageing resistance to heat humidity and many chemicals
- Good loading characteristics
- Easy processing characteristics
- The thixotropy of the Eratrowel systems are sufficient to prevent sagging which makes them an ideal repair material for vertical surfaces too.
- Excellent for water proofing and filling large gaps where water may permeate through.
- Applied on site without any special equipment requirements.

3 Component TDI/Polyether

Both TDI systems Eratrowel 83A and Eratrowel 93A have longer working lives than the MDI system so should be used when a longer pot life is required.

2 Component MDI/Polyether

Erapol Eratrowel MT70AFR - A polyether based polyurethane repair compound with a working life of 10 – 12 minutes, it contains additives that enable the elastomer to have fire retardant and anti-static properties.

Eratrowel MT80A – A high performance cold trowellable polyurethane, once mixed it becomes a trowellable paste in 1 – 2 minutes with a pot life of 8 minutes cures at room temperature.

